

## Tubo Pro Pendant

53W / 4690lm / 3500K / DALI / Wide flood  
76° / 2984mm

64931




Design: Eduardo Souto de Moura  
Pendant luminaire with tubular semi frosted PMMA body with 70mm diameter.  
Clear polycarbonate end caps with marked installation angles.  
Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.  
Equipped with 2m cable (5x0.75 mm²).  
Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP44 | 230Vac | 50/60Hz



LED	3500K	Light Source	Luminaire
Power		53W	62,4W
Flux		6900lm	4690lm
Efficiency		130lm/W	75lm/W
LOR		-	68%
UGR		-	<16



Beam angle  
Wide flood 76°  
Application  
Weight



### Finishes

○ .01 White / RAL 9010

### Mandatory

59147 Pendant fitting accessory (>2000mm)

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class D  
Model Identifier 4053560234

