

83W / 7345lm / 3500K / DALI / Wide flood
76° / 2984mm

64932




Design: Eduardo Souto de Moura
 Pendant luminaire with tubular semi frosted PMMA body with 70mm diameter.
 Clear polycarbonate end caps with marked installation angles.
 Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.
 Equipped with 2m cable (5x0.75 mm²).
 Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
 Power supply included.
 IP44 | 230Vac | 50/60Hz



LED	3500K	Light Source	Luminaire
Power	83W	95,4W	
Flux	10800lm	7345lm	
Efficiency	130lm/W	77lm/W	
LOR	-	68%	
UGR	-	<19	



Beam angle
 Wide flood 76°

Application

Weight

mm

Finishes

.01 White / RAL 9010

Mandatory

59147 Pendant fitting accessory (>1600mm)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class D
 Model Identifier 4053560234

