

Tubo Pro Pendant

34W / 3195lm / 4000K / DALI / Wide flood
76° / 1256mm

64934



Design: Eduardo Souto de Moura
Pendant luminaire with tubular semi frosted PMMA body with 70mm diameter.
Clear polycarbonate end caps with marked installation angles.
Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.
Equipped with 2m cable (5x0.75 mm²).
Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP44 | 230Vac | 50/60Hz



| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 34W | 39,1W |
| Flux | | 4700lm | 3195lm |
| Efficiency | | 142lm/W | 82lm/W |
| LOR | | - | 68% |
| UGR | | - | <19 |



Beam angle
Wide flood 76°
Application
Weight



Finishes
○ .01 White / RAL 9010

Mandatory
59146 Pendant fitting accessory

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class D
Model Identifier 4053560084