

## inVision35 Surface/Pendant

19W / 795lm / 2700K / DALI / Spot 17° / 911mm

65346



Design: O/M + Bartenbach GmbH Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.


Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories for pendant version ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



| 2700K      | Light Source | Luminaire |
|------------|--------------|-----------|
| Power      | 19W          | 23W       |
| Flux       | 1810lm       | 795lm     |
| Efficiency | 96lm/W       | 34lm/W    |
| LOR        | -            | 44%       |
| UGR        | -            | <10       |



Beam angle Spot 17° Application Weight 1,8Kg

mm

Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Mandatory 54036 Pendant direct fitting acessory 56051 Clear Base DALI ø60x35mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

