


## inVision45 **Recessed Wallwasher**

26W / 1830Im / 2700K / On/Off / Wallwasher / 1215mm

65484



Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with texturedfinish.


Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



2700K	Light Source	Luminaire
Power	26W	30,7W
Flux	2410lm	1830lm
Efficiency	96lm/W	60lm/W
LOR	-	76%
UGR	-	-

• • • • •







## Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Mandatory 51027 Recessed fitting acessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com