

26W / 1250lm / 4000K / DALI / Spot 17° /
1211mm

65614



Design: O/M + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source.

Fitting accessories for pendant version ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam

Power supply included.


IP20 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		26W	30,7W
Flux		2845lm	1250lm
Efficiency		113lm/W	41lm/W
LOR		-	44%
UGR		-	<10

Beam angle
Spot 17°

Application

Weight
2,5Kg

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com