

6,6W / 720lm / 4000K / DALI / Flood 65° /  
617mm

75052

Module with linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.


Available in white (.04) and black (.05)



LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP20 | 48Vdc




	<b>4000K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	<b>6,6W</b>	<b>8,3W</b>	
<b>Flux</b>	<b>900lm</b>	<b>720lm</b>	
<b>Efficiency</b>	<b>136lm/W</b>	<b>87lm/W</b>	
<b>LOR</b>	-	<b>80%</b>	
<b>UGR</b>	-	<b>&lt;13</b>	



Beam angle  
Flood 65°

Application



Weight

1 mm

Finishes

- .04** Matt White
- .05** Matt Black

Optional

**70045** Modules removal tool  
20x75mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class D  
Model Identifier 4053560084L

